

Package: httpproblems (via r-universe)

September 18, 2024

Title Report Errors in Web Applications with 'Problem Details' (RFC 7807)

Version 1.0.1.9000

Description Tools for emitting the 'Problem Details' structure defined in 'RFC' 7807 <<https://tools.ietf.org/html/rfc7807>> for reporting errors from 'HTTP' servers in a standard way.

License Apache License (>= 2)

Suggests tinytest

URL <https://github.com/atheriel/httpproblems>

BugReports <https://github.com/atheriel/httpproblems/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Repository <https://atheriel.r-universe.dev>

RemoteUrl <https://github.com/atheriel/httpproblems>

RemoteRef HEAD

RemoteSha 29f9ffef31aa8fc223750897735eec5de740602

Contents

http_problem	2
http_problem_types	3
stop_for_http_problem	3

Index	6
--------------	----------

 http_problem

Describe a Problem with an HTTP Request

Description

http_problem() creates the "Problem Details" structure defined in [RFC 7807](#), used for reporting errors from HTTP APIs in a standard way.

There are also helper methods for the most common HTTP problems: HTTP 400 Bad Request, 404 Not Found, 401 Unauthorized, 403 Forbidden, 409 Conflict, and 500 Internal Server Error.

Usage

```

http_problem(
    detail = NULL,
    status = 500L,
    type = NULL,
    title = NULL,
    instance = NULL,
    ...
)

bad_request(detail = NULL, instance = NULL, ...)

unauthorized(detail = NULL, instance = NULL, ...)

forbidden(detail = NULL, instance = NULL, ...)

not_found(detail = NULL, instance = NULL, ...)

conflict(detail = NULL, instance = NULL, ...)

internal_server_error(detail = NULL, instance = NULL, ...)

```

Arguments

detail	A human-readable string giving more detail about the error, if possible.
status	The HTTP status code appropriate for the response.
type	A URL pointing to human-readable documentation for this type of problem. When NULL, the type is generated based on the status code; see http_problem_types() for a list of the defaults.
title	A " short, human-readable summary of the problem type ". When NULL, the title is generated based on the status code; see http_problem_types() for a list of the defaults.
instance	A URL that identifies the specific occurrence of the problem, if possible. When NULL this field is simply excluded.
...	Additional fields added to the problem as Extension Members .

Value

An object of class "http_problem", which has fields corresponding to [an RFC 7807 Problem Details structure](#).

See Also

[stop_for_http_problem](#) for issuing R errors with these structures.

Examples

```
body <- bad_request("Parameter 'id' must be a number.")
str(body)
```

http_problem_types *List Built-In Problem Types*

Description

Many APIs will not need to define custom problem "types", since HTTP status codes **are usually illustrative enough**. This function lists the default type and title information for a given status code.

Usage

```
http_problem_types()
```

Value

A data frame of HTTP status codes and their default title & type.

stop_for_http_problem *Signal an Error Caused by an HTTP Problem*

Description

The various `stop_for_*`(`)` functions leverage R's condition system to signal an error with a custom type embedding the "Problem Details" structure defined in [RFC 7807](#).

They can be used for reporting errors from HTTP APIs in a standard way.

There are also helper methods for the most common HTTP problems: HTTP 400 Bad Request, 404 Not Found, 401 Unauthorized, 403 Forbidden, 409 Conflict, and 500 Internal Server Error.

Usage

```

stop_for_http_problem(
    detail = NULL,
    status = 500L,
    type = NULL,
    title = NULL,
    instance = NULL,
    ...
)

stop_for_bad_request(detail = NULL, instance = NULL, ...)

stop_for_unauthorized(detail = NULL, instance = NULL, ...)

stop_for_forbidden(detail = NULL, instance = NULL, ...)

stop_for_not_found(detail = NULL, instance = NULL, ...)

stop_for_conflict(detail = NULL, instance = NULL, ...)

stop_for_internal_server_error(detail = NULL, instance = NULL, ...)

```

Arguments

detail	A human-readable string giving more detail about the error, if possible.
status	The HTTP status code appropriate for the response.
type	A URL pointing to human-readable documentation for this type of problem. When NULL, the type is generated based on the status code; see http_problem_types() for a list of the defaults.
title	A "short, human-readable summary of the problem type" . When NULL, the title is generated based on the status code; see http_problem_types() for a list of the defaults.
instance	A URL that identifies the specific occurrence of the problem, if possible. When NULL this field is simply excluded.
...	Additional fields added to the problem as Extension Members .

Value

These functions call `stop()` with a custom [condition](#) (with class "http_problem_error"), so they do not return a value.

See Also

[http_problem](#) for creating the structure directly.

Examples

```
tryCatch(  
  stop_for_bad_request("Parameter 'id' must be a number."),  
  error = function(e) {  
    str(e)  
  }  
)
```

Index

`bad_request (http_problem)`, 2

`condition`, 4

`conflict (http_problem)`, 2

`forbidden (http_problem)`, 2

`http_problem`, 2, 4

`http_problem_types`, 3

`http_problem_types()`, 2, 4

`internal_server_error (http_problem)`, 2

`not_found (http_problem)`, 2

`stop_for_bad_request`
 (`stop_for_http_problem`), 3

`stop_for_conflict`
 (`stop_for_http_problem`), 3

`stop_for_forbidden`
 (`stop_for_http_problem`), 3

`stop_for_http_problem`, 3, 3

`stop_for_internal_server_error`
 (`stop_for_http_problem`), 3

`stop_for_not_found`
 (`stop_for_http_problem`), 3

`stop_for_unauthorized`
 (`stop_for_http_problem`), 3

`unauthorized (http_problem)`, 2